## **MATERIAL SAFETY DATA SHEET**

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DIS	TRIBU	ITOR'S INFORMATIO	N				
NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special	pecial HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B						
Manufactured For: Aramsco	DO	DOT Hazard Classification: ORM-D					
Address: 1655 Imperial Way	lde	Identity (trade name as used on label):					
Address: Thorofare, NJ 08069		Aramsco RAMTACK Adhesive					
Phone: 856-848-5330	MS	MSDS Number: A06639 Revision- 4					
Emergency Response Number:		te Prepared: 07/26/04	Prepared By: DL/TR/IB				
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA		Information Calls: (770)422-2071			,		
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION							
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **	
ACETONE		67-64-1	No	1000	750	d	
HEPTANE		142-82-5	No	500	500	d	
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d	
		74-98-6	No	1000	1000	d	
				1000	.000		
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.820							
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.80		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Density (Air = 1): N/E		poration Rate (	= 1):	N/E	cratare). 14/7	·	
Solubility in Water: Partial		ter Reactive: No	_ 1).	10/2			
Appearance and Odor: Straw colored liquid with ketone solvent odor.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
		o Ignition Temperature Flammability Limits in Air by % in Volume:				in Volume:	
(aerosols) EXTREMELY FLAMMABLE	iaio ig	N/E		% LEL: N/E % UEL: N/E			
FLASH POINT AND METHOD USED (non-aerosols): N/A	SPE					–	
( daily all 11102 0022 ( daily daily 1117)		SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. Use water fog to cool containers to prevent rupturing & exploding containers. Provide					
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.		shielding for personnel.					
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [ X ] STABLE [ ] UNSTABLE HAZARDOUS POLYMERIZATION [ ] WILL [ X ] WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Strong oxidizing agents.  Conditions to Avoid: Open flame, welding arcs, heat, sparks.							
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS							
Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible							
unconsciousness or asphyxiation.							
Eye Contact: Irritation.  Skin Contact: Irritation due to defatting of skin.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation of vapors may cause							
nerve damage.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in positive pressure mode.							
Protective Gloves: Neoprene. Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE  Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or							
_ ·	o with	suitable medium. In	cinerate (	or Iandfill ac	coraing to lo	cai, state or	
federal regulations. DO NOT FLUSH TO SEWER.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.							
Remove ignition sources							